



mojino

**Manufacturer of all types
of modems: OPTICAL FIBER,
TDLTE, 5G,..**



MOJINNO MA8245H2

Product Details:

Mojinno MA8245H2 provides these features:

GPON Port

- Class B+
- Receiver sensitivity: -27dBm
- Wavelengths: US 1310 nm, DS 1490 nm
- Wavelength blocking filter (WBF)
- Flexible mapping between GEM Port and TCONT
- GPON: consistent with the SN or password authentication defined in G.984.3
- Bi-directional FEC
- SR-DBA and NSR-DBA

Ethernet Port

- Ethernet port-based VLAN tags and tag removal
- 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission
- QinQ VLAN
- Limit on the number of learned MAC addresses
- MAC address learning

POTS Port

- Maximum REN: 4
- G.711A/|, G.729a/b, and G.722 encoding/decoding
- T.30/T.38/G.711 fax mode
- DTMF
- Emergency calls (with the SIP protocol)

USB Port

- USB2.0
- FTP- based network storage

WLAN

- IEEE 802.11 b/g/n
- 2 x2 MIMO
- Antenna gain: 2 dBi
- WMM

- Multiple SSIDs
- WPS
- Air interface rate: 300 Mbps

Smart interconnection

- Smart Wi-Fi coverage (V300R015C10)
- SIP/H.248 auto-negotiation
- Any port any service
- Parental control (V300R015000)
- L2/L3 forwarding:1G uplink, 2G downlink

Smart service

- Smart Wi-Fi sharing:
- Portal802.1x authentication (V300R015C10)
- SoftGRE-based sharing (V300R015C10)
- Association of one account with wo POTS ports

Smart O&M

- IPTV video quality diagnosis (V300R015c10)
- Variable-length OMCI messages
- Active/Passive rogue ONT detection and isolation
- Call emulation, and circuit test and loop-line test
- PPPoE/DHCP simulation testing

- WLAN emulation

Layer 3 Features

- PPPoE/DHCP simulation testing
- WLAN emulation
- PPPoE/Static IP/DHCP
- NAT/NAPT
- Port forwarding
- ALG, UPnP
- DDNS /DNS server/DNS client
- IPv6/Pv4 dual stack, and DS-Lite
- Static/Default routes
- Multiple services on one WAN port

Multicast

- IGMP V2v3 proxy (V300R015C00)/snooping
- MLD v1/v2 snooping
- Multicast services through Wi-Fi

Qos

- Ethernet port rate limitation
- 802.1p priority
- SP/WRR/SP+WRR
- Broadcast packet rate limitation

Security


- SPI firewall
- Filtering based on MAC/IP/URL addresses

Common O&M

- OMCI/Web UI/TR069
- Dual-system software backup and rollback

Power Saving

- Indicator power saving
- Scheduled Wi-Fi shutdown (V300R01500)



Specification

Dimensions (L x W x H)	176x 138.5 mm x28mm (without an external antenna)
Operating temperature	0C to +40*C
Operating humidity	5% RH to 95% RH (non-condensing)
Power adapter input	100-240 V AC, 50/60 Hz
System power supply	11-14 VDC, 1.5A
Static power consumption	5.5W
Maximum power consumption	16.5W
Ports	2POTS + 4GE +2.4G Wi-Fi+ 1USB
Indicators	POWER/PON/LOS/LAN/TEL/ USB/WLAN/WPS

Contact Us

Tel: +98-021-91089012

Web: www.mojinno.com

Email: info@mojinno.com

